

**LDDE Vari\*Lux***Moving Light for 48 Volt Rail*

## SPECIFICATION

|  |  |
|--|--|
| <b>Supply Voltage</b>                            | 48V DC                                     |
| <b>Powerconsumption</b>                          | ca. 40 W                                   |
| <b>compatible to Stucchi Evo</b>                 | ✓  |
| <b>LED Modul</b>                                 | Dynamic White   20W   1500lm               |
| <b>Colortemperature</b>                          | 2700-6000K   Ra > 90                       |
| <b>Casambi</b>                                   | optional   Artikelnummer 17265950541       |
| <b>Control</b>                                   | USITT DMX 512/1990                         |
| <b>DMX Channels</b>                              | 5   Intensity   White   Pan   Tilt   Focus |
| <b>8-bit resolution</b>                          | ✓  |
| <b>Seperate controll for Color and intensity</b> | ✓  |
| <b>pan and tilt range</b>                        | Pan 0-340 Grad   Tilt aprox. +-120 Grad    |
| <b>PWM Frequency</b>                             | 1000 Hz                                    |
| <b>direction control   position control</b>      | ✓   –                                      |
| <b>fanless</b>                                   | ✓  |
| <b>Focus</b>                                     | 15-50 Grad                                 |
| <b>Weight / Dimension</b>                        | 940g / L 109 H 125mm x B 133,4 mm Ø 63mm   |
| <b>protection class</b>                          | IP 20                                      |
| <b>Standalone Mode</b>                           | ✓  |

